
shielde<u>x</u>



Shieldex® 33/10

20012103310

Material Polyamide / Nylon 6

Metal Plated 99.9 % Pure Silver

Yarn count raw $33/10 \pm 2 \text{ dtex}$

Yarn count silverized $40/10 \pm 2 \text{ dtex}$

Twist Z 120

Electrical Resistivity $\leq 4 \text{ k}\Omega/\text{m}$

Yield $250.000 \text{ m/kg} \pm 6 \%$

Tenacity $36 \pm 7 \, \text{cN/tex}$

Elongation / Break $35 \pm 8 \%$

Make Up On cones 230 mm 3° 30

Packaging Average 560 g net yarn per cone

15 or 30 cones per carton

Storage and Handling According to our care and handling instructions

Compliance and Certification OEKO-TEX® Standard 100, DIN EN ISO 9001:2015, REACH, RoHS.

Alterations Reserved 19.01.22/05 — The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

